TRADE FORCE®

Any job, anywhere.

Two-pole Voltage and Continuity Electrical Tester

AC/DC Voltage | Coutinuity | IP54

Quick and Easy Test on Multiple Electrical Indicators

- ► AC/DC voltage test with clear LED indication
- ► Polarity detection
- ► Rotary field indication
- ► Low impedance test
- ► Single pole phase test

Designed for Safety

- ► Insulated cap for probes protection and storage
- ► RCD button to switch off all the power once there is electrical danger or accident

Trustworthy Quality

- ► Safe to use in rainy or moist places and environment with IP54 level waterproof and dustproof
- ► CE qualification



0004940002

EN 61010-1
CAT II 1000V

EN 61010-1
CAT III 600V

Certificates

CE ROHS Reach

Two-pole Voltage and Continuity Electrical Tester

This tester is designed to test AC/DC voltage and continuity.



- Instant testing results
- Clear voltage range indication
- Safety button to close all the power in case of emergency
- Insulated probe cover for storage

General Specifications			
Voltage test	Yes	**Flashlight**	Yes
Continuity test	Yes	**200 kΩ input impedance**	Current draw 3,5 mA @ 690 V Current draw 1,15 mA @ 230 V
Voltage AC / DC	12 - 400 V AC / DC, 12 - 690 V DC	**7k Ω input impedance (with load buttons pressed)**	Current draw 30 mA @ 230 V
Continuity range	0 - 400 Ω	**Safety rating (EN60101-1)**	CAT II 1000 V, CAT III 600 V
Frequency	0 - 60 Hz	**Working Environment**	Temperature - 10 ~ 55 °C, Humidity max 85%
Internal Impedance	< 200 kΩ	**Storage Environment**	Temperature - 10 ~ 55 °C, Humidity max 85%
Phase rotation	200 V - 440 V	**IP rating (water and dust-proof)**	IP54
Display	LED indication	**Shell material**	ABS, PC, TPE
Response Time (LED indicator)	< 0.1 s	**Color**	Black / blue
Continuity test —visual results	Yes	**Battery type**	2 X AAA battery
Continuity test —audible results	Yes	**Battery life**	24 hours
Display hold	Yes	**Net weight**	254 g
Indication of polarity	Yes	**Size (L x W x H)**	240 * 78 * 40 mm
Single pole test for phase detection	Yes	**Warranty**	2 Years
Rotary field indicator	Yes	**Qualification**	CE, Reach
Probe tip protection	Yes	**Warranty**	2 years
Voltage detection with discharged battery	Yes	**Accessories**	Test leads, 2 X AAA battery, carrying case, manual
Wear indicator test lead wire	Yes		